

EXILED 138 25M EMERGENCY LIGHT

ExiLED 138

ExiLED 138 is an elegant and functional emergency light in aluminium and plexi glass for indoor installation. Suits perfect for applications like office buildings, cinema, hotel, shopping centers, cafe and restaurants.

Unique raster layer technology ensures evenly and comfortable light distribution on the sign

ExiLED 138 is designed for both new building construction and renovation of existing facilities. Luminaire and pictogram must be ordered separately.

ExiLED 138 supplied with product variants for reading distance upto 40 meters, see separate data sheets.

ExiLED 138 is possible to be used as maintained or non-maintained luminaire.

ExiLED 138 can be provided with interfaces towards;

- Potential free contacts



FEATURES & BENEFITS

- LED based exit sign with dimming function
- Delivered as self-contained/auto test luminaire
- Choice of 1, 3 or 8 hour autonomy via DIP switch
- IP 40 – dustproof luminaire
- Read distance upto 25 meters.
- High lumen output – 1h = 180lm, 3h = 110lm, 8h = 40lm
- Technical lifetime of LED > 100 000 hours
- Simple and quick assembly and maintenance



EXILED 138 25M EMERGENCY LIGHT

TECHNICAL DATA	
Reading distance, exit sign	Two-sided 25m
Voltage	220-240VAC / 50-60Hz
Power consumption	3.3W / 3.5VA
Battery	3.6V/1.2Ah NiMH
Battery protection	Over charge protection /deep discharge protection
Charging Time	16 hours
Battery back-up time	1 hour / 3 hours / 8 hours (from dip switch)
Light source	15 LED
Technical lifetime (light source)	>100 000 hours
Lumen output, mains	150lm
Lumen output, emergency (1h / 3h / 8h)	180 / 110 / 40 lm
Approvals	EN 60598-1, EN 60598-2-22, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
Ambient temperature	5 to 40 °C
Humidity	Up to 95%
IK rating	IK08
IP rating	IP40
Dimensions	265 x 53 x 222 mm
Weight	540 / 742 gr
Colour	Anodized aluminum / black plastic
Materials	Aluminum, Acrylic Plate
Mounting method	Ceiling, wall bracket, suspended, pendulum, flag mount

MODEL NO	DESCRIPTION
138087	ExiLED MST LED 25m 230V w/pict 138h
290080.1	ExiLEDpictogram 22m two-sided arrow D
290080.2	ExiLEDpictogram 22m two-sided arrow R
290080.3	ExiLEDpictogram 22m two-sided arrow U
290080.4	ExiLEDpictogram 22m one-sided arrow D
290080.5	ExiLEDpictogram 22m one-sided arrow R
290080.6	ExiLEDpictogram 22m one-sided arrow L
290080.7	ExiLEDpictogram 22m one-sided arrow U
290080.110	ExiLEDpictogram 22m two-sided arrow R-D
290080.120	ExiLEDpictogram 22m two-sided arrow R-U
290080.130	ExiLEDpictogram 22m one-sided arrow R-D
290080.140	>ExiLEDpictogram 22m one-sided arrow R-U
290080.150	ExiLEDpictogram 22m one-sided arrow L-D
290080.160	ExiLEDpictogram 22m one-sided arrow L-U
290080.11	ExiLEDpictogram HC 22m two-sided arrow D

EXILED 138 25M EMERGENCY LIGHT

290080.21	ExiLEDpictogram HC 22m two-sided arrow U
290080.31	ExiLEDpictogram HC 22m two-sided arrow U
290080.41	ExiLEDpictogram HC 22m one-sided arrow D
290080.51	ExiLEDpictogram HC 22m one-sided arrow R
290080.61	ExiLEDpictogram HC 22m one-sided arrow L
290080.71	ExiLEDpictogram HC 22m one-sided arrow U
290180	3.6V / 1.2Ah NiMH
29008X.STR	ExiLED 22 diode matrix
290186	Exi-/MaxLED wall bracket
290187	ExiLED flag mounting bracket
290189	>Exi-/MaxLED pendulum suspension kit 1 m
290191	Exi-/MaxLED wire suspension kit 4 m
290188	ExiLED spacer for ceiling mounting
290192	ExiLED 22 protection grid
290087.1	ExiLED 22 kit for recessed mounting
290195	ExiLED22 unloading plate
290099	Plug-in module potential free

For more information,

<https://honeywellbuildings.in>

Call: 1-800-103-0339

Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002

www.honeywell.com

© 2020 Honeywell International Inc.

**EXILED 138 25M
EMERGENCY LIGHT**

Honeywell