

EXILED 138 40M EMERGENCY LIGHT

ExiLED 138

ExiLED 138 is an elegant and functional emergency light in aluminium and plexi glass for indoor installation. Suits perfect for applications like office buildings, cinema, hotel, shopping centers, cafe and restaurants

Unique raster layer technology ensures evenly and comfortable light distribution on the sign

ExiLED 138 is designed for both new building construction and renovation of existing facilities. Luminaire and pictogram must be ordered separately.

ExiLED 138 supplied with product variants for reading distance upto 40 meters, see separate data sheets.

ExiLED 138 is possible to be used as maintained or non-maintained luminaire.

ExiLED 138 can be provided with interfaces towards;

- Potential free contacts



FEATURES & BENEFITS

- LED based exit sign with dimming function
- Delivered as self-contained/auto test luminaire
- Choice of 1, 3 or 8 hour autonomy via DIP switch
- IP 40 – dustproof luminaire
- Read distance upto 25 meters.
- High lumen output – 1h = 180lm, 3h = 110lm, 8h = 40lm
- Technical lifetime of LED > 100 000 hours
- Simple and quick assembly and maintenance



EXILED 138 40M EMERGENCY LIGHT

TECHNICAL DATA	
Reading distance, exit sign	Two-sided 40m
Voltage	220-240VAC / 50-60Hz
Power consumption	3.3W / 3.5VA
Battery	3.6V/1.2Ah NiMH
Battery protection	Over charge protection /deep discharge protection
Charging Time	16 hours
Battery back-up time	1 hour / 3 hours / 8 hours (from dip switch)
Light source	18 LED
Technical lifetime (light source)	>100 000 hours
Lumen output, mains	180lm
Lumen output, emergency (1h / 3h / 8h)	210 / 110 / 40lm
Approvals	EN 60598-1, EN 60598-2-22, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
Ambient temperature	5 to 40 °C
Humidity	Up to 95%
IK rating	IK08
IP rating	IP40
Dimensions	366 x 53 x 272 mm
Weight	690 / 906 gr
Colour	Anodized aluminum / black plastic
Materials	Aluminum, Acrylic Plate
Mounting method	Ceiling, wall bracket, suspended, pendulum mount

MODEL NO	DESCRIPTION
138126	ExiLED MST LED 40m 230V w/pict 138h
290120.1	ExiLED pictogram 34m two-sided arrow D
290120.2	ExiLED pictogram 34m two-sided arrow R
290120.3	ExiLED pictogram 34m two-sided arrow U
290120.4	ExiLEDpictogram 22m one-sided arrow D
290120.5	ExiLED pictogram 34m one-sided arrow R
290120.6	ExiLED pictogram 34m one-sided arrow L
290120.7	ExiLED pictogram 34m one-sided arrow U
290180	3.6V/ 1.2Ah NiMH
29012X.STR	ExiLED 34 diode matrix
290186	Exi-/MaxLED wall bracket
290187	ExiLED flag mounting bracket
290189	Exi-/MaxLED pendulum suspension kit 1 m

EXILED 138 25M EMERGENCY LIGHT

290191	Exi-/MaxLED wire suspension kit 4 m
290188	ExiLED spacer for ceiling mounting
290193	ExiLED 34 protection grid
290099	Plug-in module potential free

For more information,

<https://honeywellbuildings.in>

Call: 1-800-103-0339

Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002

www.honeywell.com

© 2020 Honeywell International Inc.

**EXILED 138 40M
EMERGENCY LIGHT**

Honeywell