

# MAXLED 26M 138 EMERGENCY LIGHT

## MaxLED 138

**MaxLED 138** is an elegant and functional emergency light in aluminium for indoor installation. Suits perfect for applications like schools, shopping malls, warehouses, industrial and sports halls, terminal buildings etc.

**MaxLED 138** is designed for both new building construction and renovation of existing facilities.

**MaxLED 138** is available with single or double-sided pictograms.

**MaxLED 138** supplied with product variants for reading distance of 26 meters and 65 meters, see separate data sheets.

**MaxLED 138** has a slit on the underside of the housing. It can also work as a guide light

**MaxLED 138** can be provided with interfaces towards;

- Potential free contacts



## FEATURES AND BENEFITS

- LED based marker lights
- Delivered as self-contained/auto test luminaire
- Choice of 1, 3 or 8 hour autonomy via DIP switch
- Simple and quick assembly and maintenance
- IP 40 – dustproof luminaire
- High lumen output – 1h = 250lm, 3h = 110lm, 8h = 40lm
- Reading distance of 26 meters.
- Technical lifetime of LED > 100 000 hours



# MAXLED 26M 138 EMERGENCY LIGHT

TECHNICAL DATA	
Reading distance, exit sign	Two-sided 26m
Voltage	220-240VAC / 50-60Hz
Power consumption	4.2W / 4.4VA
Battery	3.6V/1.2Ah NiMH
Battery protection	Over charge protection / deep discharge protection
Charging Time	16 hours
Battery back-up time	1 hour / 3 hours / 8 hours (from dip switch)
Light source	24 White LED
Technical lifetime (light source)	>100 000 hours
Lumen output, mains	280lm
Lumen output, emergency (1h / 3h / 8h)	250 / 110 / 40 lm
Approvals	EN 60598-1, EN 60598-2-22, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
Ambient temperature	5 to 40 °C
Humidity	Up to 95%
IK rating	IK03
IP rating	IP40
Dimensions	330 x 52 x 230 mm
Weight	1068/ 1409 gr
Colour	Anodized aluminum / grey plastic
Materials	Aluminum, Plexiglass, PC/ABS
Mounting method	Ceiling, wall bracket mounting base

MODEL NO	DESCRIPTION
138009	MaxLED M ST LED 26m 230V w/pict 138h
290180	Battery 3.6V / 1.2Ah NiMH
290264.1	MaxLED pictogram 26m Arrow D
290264.2	MaxLED pictogram 26m Arrow R
290264.3	MaxLED pictogram 26m Arrow L
290264.4	MaxLED pictogram 26m Arrow U
290299	Protection Grid for MaxLED 26m
290331	MaxLED 26m back part for 1-sided
290295	Flag Mounting Accessory for MaxLED
290099	Plug-in module potential free

## For more information,

<https://honeywellbuildings.in>

Call: 1-800-103-0339

Email: [HBT-Indiabuildings@honeywell.com](mailto:HBT-Indiabuildings@honeywell.com)

## Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,  
Block C, Sushant Lok Phase - I,  
Gurgaon - 122 002

[www.honeywell.com](http://www.honeywell.com)

© 2020 Honeywell International Inc.

**MAXLED 26M 138  
EMERGENCY LIGHT**

**Honeywell**