

NF-SP100CI/ UL


2W Compact Ceiling Loudspeaker

NF-SP100CI/UL is an all-purpose 2W ceiling speaker with an excellent audio performance and aesthetic appealing enclosure. This speaker features a high sound pressure level and a wide frequency response and low distortion for high sound level suitable for speech and music reproduction.

NF-SP100CI/UL has two spring clamps which can be used to easily fix the speaker into the false ceiling. It has three power taps (2/1/0.5/0.25W) with the built in 70V transformer. The round ABS grille is well fitted in the front.



FEATURES & BENEFITS

- UL certified 
- Flush-mounting system for fast and easy installation
- Wide frequency response for excellent speech and music reproduction
- Excellent crash and rust resistant design
- Fully ABS plastic with ABS grille
- Power tapping options available – 2/1/0.5/0.25W

NF-SP100CI/UL TECHNICAL SPECIFICATIONS

Rated Power / Max Power: 2W / 3W

Power Taps: 2W / 1W / 0.5W / 0.25W

Rated Voltage: 70 V

Sound Pressure Level at 1w (1m & 1kHz): 80 ± 4 dB **Rated**

Impedance: 2450 Ω / 4900 Ω / 9800 Ω / 19600 Ω

Frequency Response: 125Hz – 16kHz

(-10 dB with reference to 1kHz)

SPL at rated power/1W: 82dB / 85dB (1m & 1kHz)

Size of Speaker (dia): 140 mm **Hole**

cut out: 118 mm

Magnet Weight: 50 gm (±10 gm)


Connection: 5 Pole screw connector

Dimension: 140 mm X 70 mm **Color:**


Opal White

Weight of Speaker: 400 gm

Frequency Response



Circuit Diagram



For more information,
<https://honeywellbuildings.in>
Call: 1-800-103-0339
Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings
Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurgaon - 122 002

www.honeywell.com

© 2020 Honeywell International Inc.

NF-SP100CI/
UL

Honeywell